



A brand of Indo Spark Group Since 1978

Chemical Anchor Fasteners



CM350P

(Polyester)

- Applicable for rebar and stud upto 16mm
- Available in side by side cartridges (350 ml)
- Ratio 10:1



CM350VESF

(Vinylester)

- Applicable for rebar and stud upto 24mm
- Available in side by side cartridges (350 ml)
- Ratio 10 : 1





CM360SH

(Seismic Hybrid)

- Applicable for rebar and stud upto 40mm
- Available in side by side cartridges
- (360 ml) Ratio 10 : 1





CM585PE-Pro

(Pure Epoxy)

- Applicable for rebar and stud upto 40mm
- Available in side by side cartridges (585 ml)
- Ratio 3:1



Chemical Anchor Stud (CAS)



Grade 5.8 & 8.8. SS304 and SS316

- · For non-cracked concrete
- · For dry and water saturated concrete Anchor Stud length longer than one meter (1000mm) can be manufactured on specific request

Super Cap-Capsule



· Heavy duty anchor with small spacing and edge distances: installed by spinning

Mechanical Anchor Fasteners

All range cold formed -5.8, 8.8, SS304 and SS316

Through Bolt Anchor TBA



- For used in concrete
- For medium high loads

Indo Wedge Anchor **IWA**



- For non-cracked concrete
- For high loads

Blow out pump



For cleaning dust from drilled holes prior to applying bonded anchors or installing mechanical anchors

Chemical Mixer Nozzle

Неменеры

 Static mixer for bonded anchors in cartridges

Indo Prime Bolt Zone

IPBZ

- For cracked and non-cracked concrete
- For high loads

Dispenser Gun

DM350 DM400 DM585



Cleaning brush



· For cleaning out holes prior to anchor installation





 Internal threaded DIA for simple hammer - set installation





A brand of Indo Spark Group Since 1978

Nylon Anchor Fasteners All range cold formed -5.8, 8.8, SS304 and SS316



Nylon Plug NFP



- For use in all base material
- Screws made of SS, anti-corrosion

Nylon FD Plug



· For use in all base material

1K Assembly Foam PRO

- Installing doors and windows
- Creation of soundproof screens and layers Improving thermal insulation in cooling systems

750 ml 18 Months Shelf life

Hex Head Screw HHS



- For use in all base material
- Screws made of SS, anti-corrosion

1K Assembly PU Foam

- Installation of doors and window air-sealing
- Seal penetrations around cables and pipes
- Fill seams between chimneys, roof protection, roof panels, and wall panels

750 ml One Time Use Only



1K Fire Rated **B1** Gun Grade PRO

- Installation of fireproof doors and windows
- Seal all openings in roof constructions
- · Fire and smoke retardant sealant between walls, floors and ceilings.

750 ml 18 Months Shelf life

Nylon Hammer Fixing Plug



- For use in all base material
- Screws made of SS, anti-corrosion



1K Fire Rated PU Foam B1

- Installation of fireproof doors and windows
- Sealing of all openings in roof constructions
- Sealing of fire-retardant joints in walls, ceilings, penetration seals, and joints.

750 ml One Time Use Only



Foam Gun Cleaner

Cleaning Spray for removal of uncured Construction Foam tools and surfaces 500 ml

Pu Foam Spray Dispensing Gun





PU Foam Spray Nozzle

For 1K Version



All Product Catalog

INDO SPARK CONSTRUCTION SERVICES

198, E ward, Tararani Chowk, Near Geeta Mandir, Kolhapur - 416 003 (Mah.India) Toll Free: 1800 123 500 023, E-mail: mail@indospark.com

Branches: Pune | Mumbai



